

CAPACIDAD (LITROS)	CAPACIDAD (m ³)	ANILLOS	CALIBRE CAL 20 = 0,90 mm CAL 18 = 1,20 mm CAL 16 = 1,50 mm CAL 14 = 1,80 mm	LAMINAS POR ANILLO	DIAMETRO (m)	ALTURA (m)
4.500	4,5	1	16	4	2,8	0,75
10.500	10,5	1	16	6	4,2	0,75
18.500	18,5	1	16	8	5,6	0,75
29.000	29,0	1	16	10	7,0	0,75
41.500	41,5	1	16	12	8,4	0,75
56.500	56,5	1	16	14	9,8	0,75
74.000	74,0	1	16	16	11,2	0,75
93.500	93,5	1	16	18	12,6	0,75
115.500	115,5	1	16	20	14,0	0,75
140.000	140,0	1	16	22	15,4	0,75
166.500	166,5	1	16	24	16,8	0,75
195.500	195,5	1	16	26	18,2	0,75
226.500	226,5	1	16	28	19,6	0,75
260.000	260,0	1	16	30	21,0	0,75
296.000	296,0	1	16	32	22,4	0,75
334.000	334,0	1	16	34	23,8	0,75
374.500	374,5	1	16	36	25,2	0,75
417.000	417,0	1	16	38	26,6	0,75
462.000	462,0	1	16	40	28,0	0,75
509.500	509,5	1	16	42	29,4	0,75
9.000	9,0	2	16-16	4	2,8	1,5
21.000	21,0	2	16-16	6	4,2	1,5
37.000	37,0	2	16-16	8	5,6	1,5
58.000	58,0	2	16-16	10	7,0	1,5
83.000	83,0	2	16-16	12	8,4	1,5
113.000	113,0	2	16-16	14	9,8	1,5
148.000	148,0	2	16-16	16	11,2	1,5
187.000	187,0	2	16-16	18	12,6	1,5
231.000	231,0	2	16-16	20	14,0	1,5
279.500	279,5	2	16-16	22	15,4	1,5
333.000	333,0	2	16-16	24	16,8	1,5
390.500	390,5	2	14-16	26	18,2	1,5
453.000	453,0	2	14-16	28	19,6	1,5
520.000	520,0	2	14-16	30	21,0	1,5
591.500	591,5	2	14-16	32	22,4	1,5
668.000	668,0	2	14-16	34	23,8	1,5
748.500	748,5	2	14-16	36	25,2	1,5
834.000	834,0	2	14-16	38	26,6	1,5

CAPACIDAD (LITROS)	CAPACIDAD (m ³)	ANILLOS	CALIBRE CAL 20 = 0,90 mm CAL 18 = 1,20 mm CAL 16 = 1,50 mm CAL 14 = 1,80 mm	LAMINAS POR ANILLO	DIAMETRO (m)	ALTURA (m)
924.500	924,5	2	14-16	40	28,0	1,5
1.019.000	1.019,0	2	14-16	42	29,4	1,5
14.000	14,0	3	16-16-16	4	2,8	2,3
31.000	31,0	3	16-16-16	6	4,2	2,3
55.500	55,5	3	16-16-16	8	5,6	2,3
86.500	86,5	3	16-16-16	10	7,0	2,3
125.000	125,0	3	16-16-16	12	8,4	2,3
170.000	170,0	3	16-16-16	14	9,8	2,3
222.000	222,0	3	16-16-16	16	11,2	2,3
281.000	281,0	3	16-16-16	18	12,6	2,3
346.500	346,5	3	16-16-16	20	14,0	2,3
419.500	419,5	3	16-16-16	22	15,4	2,3
499.000	499,0	3	16-16-16	24	16,8	2,3
586.000	586,0	3	14-16-16	26	18,2	2,3
679.500	679,5	3	14-16-16	28	19,6	2,3
780.000	780,0	3	14-16-16	30	21,0	2,3
887.500	887,5	3	14-16-16	32	22,4	2,3
1.002.000	1.002,0	3	14-16-16	34	23,8	2,3
1.123.000	1.123,0	3	14-16-16	36	25,2	2,3
1.251.500	1.251,5	3	14-16-16	38	26,6	2,3
1.386.500	1.386,5	3	14-16-16	40	28,0	2,3
1.528.500	1.528,5	3	14-16-16	42	29,4	2,3
18.500	18,5	4	16-16-16-16	4	2,8	3,0
41.500	41,5	4	16-16-16-16	6	4,2	3,0
74.000	74,0	4	16-16-16-16	8	5,6	3,0
115.500	115,5	4	16-16-16-16	10	7,0	3,0
166.500	166,5	4	16-16-16-16	12	8,4	3,0
226.500	226,5	4	16-16-16-16	14	9,8	3,0
296.000	296,0	4	16-16-16-16	16	11,2	3,0
374.500	374,5	4	16-16-16-16	18	12,6	3,0
462.000	462,0	4	16-16-16-16	20	14,0	3,0
559.000	559,0	4	16-16-16-16	22	15,4	3,0
665.500	665,5	4	16-16-16-16	24	16,8	3,0
781.000	781,0	4	14-16-16-16	26	18,2	3,0
906.000	906,0	4	14-16-16-16	28	19,6	3,0
1.040.000	1.040,0	4	14-16-16-16	30	21,0	3,0
1.183.000	1.183,0	4	14-16-16-16	32	22,4	3,0
1.335.500	1.335,5	4	14-16-16-16	34	23,8	3,0
1.497.500	1.497,5	4	14-16-16-16	36	25,2	3,0
1.668.500	1.668,5	4	14-16-16-16	38	26,6	3,0
1.848.500	1.848,5	4	14-16-16-16	40	28,0	3,0

CAPACIDAD (LITROS)	CAPACIDAD (m ³)	ANILLOS	CALIBRE CAL 20 = 0,90 mm CAL 18 = 1,20 mm CAL 16 = 1,50 mm CAL 14 = 1,80 mm	LAMINAS POR ANILLO	DIAMETRO (m)	ALTURA (m)
2.038.000	2.038,0	4	14-16-16-16	42	29,4	3,0
2.237.000	2.237,0	4	14-16-16-16	44	30,8	3,0
2.445.000	2.445,0	4	14-16-16-16	46	32,2	3,0
2.662.000	2.662,0	4	14-16-16-16	48	33,6	3,0
2.888.500	2.888,5	4	14-16-16-16	50	35,0	3,0
3.124.500	3.124,5	4	14-16-16-16	52	36,4	3,0
3.369.500	3.369,5	4	14-16-16-16	54	37,8	3,0
3.623.500	3.623,5	4	14-16-16-16	56	39,2	3,0
3.887.000	3.887,0	4	14-16-16-16	58	40,6	3,0
4.159.500	4.159,5	4	14-16-16-16	60	42,0	3,0
23.000	23,0	5	14-14-16-16-16	4	2,8	3,8
52.000	52,0	5	14-14-16-16-16	6	4,2	3,8
92.500	92,5	5	14-14-16-16-16	8	5,6	3,8
144.500	144,5	5	14-14-16-16-16	10	7,0	3,8
208.000	208,0	5	14-14-16-16-16	12	8,4	3,8
283.000	283,0	5	14-14-16-16-16	14	9,8	3,8
369.500	369,5	5	14-14-16-16-16	16	11,2	3,8
468.000	468,0	5	14-14-16-16-16	18	12,6	3,8
577.500	577,5	5	14-14-16-16-16	20	14,0	3,8
699.000	699,0	5	14-14-16-16-16	22	15,4	3,8
832.000	832,0	5	14-14-16-16-16	24	16,8	3,8
976.500	976,5	5	14-14-14-16-16	26	18,2	3,8
1.132.500	1.132,5	5	14-14-14-16-16	28	19,6	3,8
1.300.000	1.300,0	5	14-14-14-16-16	30	21,0	3,8
1.479.000	1.479,0	5	14-14-14-16-16	32	22,4	3,8
1.669.500	1.669,5	5	14-14-14-16-16	34	23,8	3,8
1.872.000	1.872,0	5	14-14-14-16-16	36	25,2	3,8
2.085.500	2.085,5	5	14-14-14-16-16	38	26,6	3,8
2.311.000	2.311,0	5	14-14-14-16-16	40	28,0	3,8
2.548.000	2.548,0	5	14-14-14-16-16	42	29,4	3,8
62.500	62,5	6	14-14-14-14-16-16	6	4,2	4,5
111.000	111,0	6	14-14-14-14-16-16	8	5,6	4,5
173.500	173,5	6	14-14-14-14-16-16	10	7,0	4,5
249.500	249,5	6	14-14-14-14-16-16	12	8,4	4,5
339.500	339,5	6	14-14-14-14-16-16	14	9,8	4,5
443.500	443,5	6	14-14-14-14-16-16	16	11,2	4,5
561.500	561,5	6	14-14-14-14-16-16	18	12,6	4,5
693.500	693,5	6	14-14-14-14-16-16	20	14,0	4,5
839.000	839,0	6	14-14-14-14-16-16	22	15,4	4,5
998.500	998,5	6	14-14-14-14-16-16	24	16,8	4,5

CAPACIDAD (LITROS)	CAPACIDAD (m ³)	ANILLOS	CALIBRE CAL 20 = 0,90 mm CAL 18 = 1,20 mm CAL 16 = 1,50 mm CAL 14 = 1,80 mm	LAMINAS POR ANILLO	DIAMETRO (m)	ALTURA (m)
1.171.500	1.171,5	6	14-14-14-14-16-16	26	18,2	4,5
1.359.000	1.359,0	6	14-14-14-14-16-16	28	19,6	4,5
1.560.000	1.560,0	6	14-14-14-14-16-16	30	21,0	4,5
1.775.000	1.775,0	6	14-14-14-14-16-16	32	22,4	4,5
2.003.500	2.003,5	6	14-14-14-14-16-16	34	23,8	4,5
2.246.000	2.246,0	6	14-14-14-14-16-16	36	25,2	4,5
2.502.500	2.502,5	6	14-14-14-14-16-16	38	26,6	4,5
2.773.000	2.773,0	6	14-14-14-14-16-16	40	28,0	4,5
3.057.500	3.057,5	6	14-14-14-14-16-16	42	29,4	4,5
129.500	129,5	7	14-14-14-14-16-16-16	8	5,6	5,3
202.000	202,0	7	14-14-14-14-16-16-16	10	7,0	5,3
291.000	291,0	7	14-14-14-14-16-16-16	12	8,4	5,3
396.500	396,5	7	14-14-14-14-16-16-16	14	9,8	5,3
517.500	517,5	7	14-14-14-14-16-16-16	16	11,2	5,3
655.000	655,0	7	14-14-14-14-16-16-16	18	12,6	5,3
809.000	809,0	7	14-14-14-14-16-16-16	20	14,0	5,3
978.500	978,5	7	14-14-14-14-16-16-16	22	15,4	5,3
1.164.500	1.164,5	7	14-14-14-14-16-16-16	24	16,8	5,3
1.367.000	1.367,0	7	14-14-14-14-16-16-16	26	18,2	5,3
1.585.500	1.585,5	7	14-14-14-14-16-16-16	28	19,6	5,3
1.820.000	1.820,0	7	14-14-14-14-16-16-16	30	21,0	5,3
2.070.500	2.070,5	7	14-14-14-14-16-16-16	32	22,4	5,3
2.337.500	2.337,5	7	14-14-14-14-16-16-16	34	23,8	5,3
2.620.500	2.620,5	7	14-14-14-14-16-16-16	36	25,2	5,3
2.920.000	2.920,0	7	14-14-14-14-16-16-16	38	26,6	5,3
3.235.500	3.235,5	7	14-14-14-14-16-16-16	40	28,0	5,3
3.567.000	3.567,0	7	14-14-14-14-16-16-16	42	29,4	5,3
148.000	148,0	8	14-14-14-14-14-16-16-16	8	5,6	6,0
231.000	231,0	8	14-14-14-14-14-16-16-16	10	7,0	6,0
333.000	333,0	8	14-14-14-14-14-16-16-16	12	8,4	6,0
453.000	453,0	8	14-14-14-14-14-16-16-16	14	9,8	6,0
591.500	591,5	8	14-14-14-14-14-16-16-16	16	11,2	6,0
748.500	748,5	8	14-14-14-14-14-16-16-16	18	12,6	6,0
924.500	924,5	8	14-14-14-14-14-16-16-16	20	14,0	6,0
1.118.500	1.118,5	8	14-14-14-14-14-16-16-16	22	15,4	6,0
1.331.000	1.331,0	8	14-14-14-14-14-16-16-16	24	16,8	6,0
1.562.000	1.562,0	8	14-14-14-14-14-16-16-16	26	18,2	6,0

CAPACIDAD (LITROS)	CAPACIDAD (m ³)	ANILLOS	CALIBRE CAL 20 = 0,90 mm CAL 18 = 1,20 mm CAL 16 = 1,50 mm CAL 14 = 1,80 mm	LAMINAS POR ANILLO	DIAMETRO (m)	ALTURA (m)
1.812.000	1.812,0	8	14-14-14-14-14-16-16-16	28	19,6	6,0
2.080.000	2.080,0	8	14-14-14-14-14-16-16-16	30	21,0	6,0
2.366.500	2.366,5	8	14-14-14-14-14-16-16-16	32	22,4	6,0
2.671.500	2.671,5	8	14-14-14-14-14-16-16-16	34	23,8	6,0
2.995.000	2.995,0	8	14-14-14-14-14-16-16-16	36	25,2	6,0
3.337.000	3.337,0	8	14-14-14-14-14-16-16-16	38	26,6	6,0
3.697.500	3.697,5	8	14-14-14-14-14-16-16-16	40	28,0	6,0
4.076.500	4.076,5	8	14-14-14-14-14-16-16-16	42	29,4	6,0